

DATA SHEET

Multiple Power Adapter 3-in-1 solution – Makes your mobile life easier

Issue April 2009

Pages 2

People who are often on business or private trips want to power up and recharge their tablet PCs and notebooks anywhere and anytime.

Fujitsu Technologie solutions goal is it to anticipate our customers' wishes and therefore we offer the Multiple Power adapter for usage at work, at home, in cars, trucks, boats and caravans. This power adapter fulfils two basic functions: charging and powering of your Pocket Loox, STYLISTIC, AMILO and LIFEBOOK Series, requiring up to 90 W – for more power on the move.

Reliability

- Quality and stability
- Constant current regulation ensures stable charging of batteries

Mobility

- Through a wide input voltage range which ensures that the Multiple Power Adapter can be used not only at home or at work but also in lorries, boats, - anywhere where 12 V, 24 V, 110V - 220V power supplies are available
- Select just the correct DC output cable and use the charger for your tablet PC or notebook



Security

- The adapter comes with short circuit protection and under voltage protection:
the Multiple Power Adapter will not enable charging if the voltage on the line is not within the specified limits
- Over voltage protection
- Over temperature protection

Diversity

Accessories for differentiated demands
Meet highest demands in terms of ergonomics and usability



Product	Multiple Power adapter 100- 240 V input, 20V, 16V, 5V output. 90W
Order code	S26391-F2613-L310
AC voltage	
Input	100 - 240 V AC +/- 5 % 50 - 60 Hz
Main output, individual	5 V DC/3 A 16 V DC/4.5 A 20 V DC/4.5 A
Output, combined	16 V DC/3.56 A + 5 V DC/3 A, 72 W 20 V DC/3.75 A + 5 V DC/3 A, 90 W
DC voltage:	
Input	12 V DC/10 A 24 V DC/8 A
Main output, individual	5 V DC/3 A (Mini USB) 5 V DC/3 A (Circular connector for Pocket LOOX 4xx, 5xx, 7xx: Cradle DC JACK, S26391-F2607-L255) 16 V DC/4.5 A 20 V DC/4.5 A
Output, combined	16 V DC/3.56 A + 5 V DC/3 A, 72 W 20 V DC/3.75 A + 5 V DC/3 A, 90 W
Output tolerance	20 V/16 V/5 V +/- 5 %
Output	90 W stable
Cigarette lighter	
Fuse	10 A/32 V MINI fuse (fast-acting type)
Measurements	
L x W x H	160 x 70 x 34 mm
Conditions of use:	
Operating temperature	5 to 35 °C
Storage temperature	-40 to 70 °C
Declaration of conformity / approval:	
 	<p>The vehicle/AC adapter satisfies the requirements of the most recent EU Directives.</p> <p>The adapter has been subjected to and passed the conformity tests described in these directives.</p> <p>The test for electromagnetic compatibility was carried out in accordance with EU Directives 89/336/EU, 91/263/EU, 92/31/EU and the standards EN55025 & FCC15 part B.</p> <p>The adapter complies with 2006/28/EC(72/245/EEC) and has type approval through the Luxemburg Ministry of Transport (type approval number e13*72/245*2006/28*4168*00).</p> <p>Although this adapter complies with the latest stringent requirements, no guarantee can be given that other devices will not be affected by the operation of this device.</p>

Information about environmental care, policies, programs and our Environmental Guideline FSC03230:
ts.fujitsu.com/aboutus
Take back and Recycling information: ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see: ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions 2009

Published by:
Fujitsu Technology Solutions
ts.fujitsu.com